


RZB

Dimensioni in mm - Dimensions in mm - Abmessungen in mm

 mm.	d₁ H14		d₂ h14		s	h max	A	
2,5	2,70	0,250 / 0	4,80	0 / -0,300	0,45	0,85	0,81	0,035
3	3,20	0,300 / 0	5,50	0 / -0,300	0,45	0,85	1,40	0,045
4	4,30	0,300 / 0	7,00	0 / -0,360	0,50	0,95	3,30	0,080
5	5,30	0,300 / 0	9,00	0 / -0,360	0,60	1,05	6,70	0,150
6	6,40	0,360 / 0	10,00	0 / -0,360	0,60	1,15	11,20	0,216
*6,35 - 1/4"	6,70	0,360 / 0	9,50	0 / -0,360	0,60	1,15		0,150
7	7,40	0,360 / 0	12,00	0 / -0,430	0,70	1,25	18,00	0,310
8	8,40	0,360 / 0	13,00	0 / -0,430	0,70	1,35	27,00	0,400
10	10,50	0,430 / 0	16,00	0 / -0,430	0,90	1,55	53,00	0,760
11-7/16"	11,60	0,430 / 0	15,90	0 / -0,430	0,90	1,55		0,611
12	13,00	0,430 / 0	18,00	0 / -0,430	1,00	1,65	93,00	0,860
*12,7 - 1/2"	13,70	0,430 / 0	19,00	0 / -0,520	1,00	1,75		0,976
14	15,00	0,430 / 0	22,00	0 / -0,520	1,10	1,95	145,00	1,706
16	17,00	0,430 / 0	24,00	0 / -0,520	1,30	2,05	230,00	1,960
18	19,00	0,520 / 0	27,00	0 / -0,520	1,40	2,25	310,00	2,721
*19 - 3/4"	20,00	0,520 / 0	30,00	0 / -0,520	1,40	2,45		4,100
20	21,00	0,520 / 0	30,00	0 / -0,520	1,40	2,45	440,00	3,630
*22 - 7/8"	23,00	0,520 / 0	33,00	0 / -0,620	1,40	2,65		4,507
24	25,60	0,520 / 0	36,00	0 / -0,620	1,60	2,85	770,00	6,120
*25,4 - 1"	27,00	0,520 / 0	38,00	0 / -0,620	1,80	3,05		7,449
*27	28,60	0,520 / 0	39,00	0 / -0,620	1,80	3,05		7,369
30	31,60	0,620 / 0	45,00	0 / -0,620	1,80	3,55	1550,00	11,070

* Non standard (prodotti su richiesta) - Non standard (product available on request) - Nichtstandard (Erzeugnisse auf Anfrage)

A Carico di prova
 Coppia torsione (Nm)
 Load Test
 Torsion Torque (Nm)
 Prüfbelastung
 Drehmoment (Nm)

Rev. 001 - 13.12.2012